

Super Lube®



SUPER LUBE® GREASE

SUPER LUBE® GREASE

Super Lube® Grease is a patented synthetic NLGI grade 2 heavy-duty, multipurpose lubricant with PTFE. Synthetic base fluids and the addition of PTFE micro powders combine to form a premium lubricant that provides longer life protection against friction, wear, rust and corrosion. Machinery lasts longer, downtime is reduced, and productivity is increased.

Super Lube® Grease is a USDA listed Food Grade lubricant, rated H-1 for incidental food contact.

Super Lube® Grease will not run or drip, does not evaporate or form gummy deposits and will not melt or separate.

Super Lube® Grease is a synthetic, heavy-duty lubricant that is compatible with most other lubricants.

Super Lube® Grease outlasts conventional greases 50-100% and has excellent adhesion.



| Part No. | Description |
|----------|------------------|
| 21006 | 6 cc Syringe |
| 21010 | ½ oz Tube |
| 21030 | 3 oz Tube |
| 21036 | 3 oz Cartridge |
| 41150 | 400 gr Cartridge |
| 41160 | 400 gr Jar |
| 41050 | 5 lb Pail |
| 41030 | 30 lb Pail |
| 41120 | 120 lb Keg |
| 41140 | 400 lb Drum |
| 82340 | 1 cc Packet |



Synco Chemical Corporation - Super Lube®
24 DaVinci Drive, Bohemia, NY 11716
Tel: (631) 567-5300 / Fax: (631) 567-5359
Email: info@super-lube.com / www.super-lube.com



Super Lube®



SUPER LUBE® GREASE

SUPER LUBE® GREASE

Super Lube® Grease Typical Applications:

- ▶ Plain, anti-friction, ball, roller, wheel bearings
- ▶ Cams, slides, valves, conveyors, chains
- ▶ Food processing equipment
- ▶ Caliper assembly and bearing grease
- ▶ Hubs, axles, chassis, shocks, springs
- ▶ Seat regulators and tracks
- ▶ Fifth wheels
- ▶ Parts lubricant
- ▶ Winches, pulleys, snaps
- ▶ Trailer and buddy bearings
- ▶ Dielectric grease, battery protector
- ▶ Campers, trailers, bicycles, guns, fishing gear, motorcycles, hunting gear
- ▶ Weight and fitness equipment
- ▶ Linkages, hinges and locks
- ▶ Lawn movers, garage doors, snow blowers, sewing machines
- ▶ Faucets and pool pumps
- ▶ Garden and farm equipment

Benefits:

- ▶ Clean, non-toxic, non-staining
- ▶ Dielectric
- ▶ USDA Rating H-1
- ▶ Will not drip, run or evaporate
- ▶ Impervious to salt water, safe in potable water
- ▶ Long lasting
- ▶ Prevents rust and corrosion while reducing friction
- ▶ Wide Temperature Range -45° to 450°F



Synco Chemical Corporation - Super Lube®
24 DaVinci Drive, Bohemia, NY 11716
Tel: (631) 567-5300 / Fax: (631) 567-5359
Email: info@super-lube.com / www.super-lube.com



**Super
Lube®**



SUPER LUBE® GREASE

SUPER LUBE® GREASE

| Typical Properties | | |
|------------------------------------|-------------|-------------------|
| Test | Test Method | Rating |
| Color | | Translucent White |
| NLGI Grade | ASTM D1092 | 2 |
| Dropping Point | ASTM D566 | >500°F (260°C) |
| Four Ball test: | ASTM D2783 | |
| Load wear index | | 81.73 kg |
| Weld Point | | 400 kg |
| Oxidation Stability 100 hrs | ASTM D942 | 0 psi |
| Wheel bearing Leakage | ASTM D1263 | 0.2 g |
| Copper Corrosion 24 hrs @ 100°C | ASTM D4048 | 1B, shiny |
| Warranty | | 24 months |

While the information contained herein is believed to be reliable, Synco Chemical Corporation makes no representation as to the reliability of the results the buyer or user will achieve.



Synco Chemical Corporation - Super Lube®
24 DaVinci Drive, Bohemia, NY 11716
Tel: (631) 567-5300 / Fax: (631) 567-5359
Email: info@super-lube.com / www.super-lube.com

